

GAS ENGINE ROLL CAGE SERIES



PRESSURE WASHERS / SINCE 1970

FEATURES

2.7 - 4.0 GPM @ 2400 to 3500 PSI
12V DC Burners



HOT WATER

OIL FIRED

BELT/DIRECT DRIVE

Hotsy-designed triplex direct-drive pump carries a 7-year warranty

12" heavy-duty flat free tires

50-ft wire-braided high pressure hose with swivel on one end

Trigger gun control with cool-grip

Model 965SS:
Oil Fired, 3.0 GPM
@ 3000 PSI

Heavy-duty regulator rectifier eliminates the need for battery

Stainless-steel coil skin provides extra durability and resists corrosion

Oil-fired Wayne burner

Lifting eyes let power equipment do the hoisting

6-gallon, removable, rust-proof polyethylene fuel tank has fuel gauge in cap

Protective Heavy-duty roll-cage chassis

Control box with adjustable temperature control, hour meter and burner on/off switch

Upstream detergent injection



Model 1075BE Compact:
4.0 GPM@ 3500 PSI;
Vanguard 400 engine; 12V
DC water heater (12V battery
required, not supplied)



MODEL	PART NO.	GPM	PSI	ENGINE	CCS	BURNER	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
871SS*	1.110-014.0	2.7	2400	Honda GX200	196	12V DC	248,500	HP3035G	43"x27"x39"	410
965SS CAL*	1.110-090.0	3.0	3000	Vanguard 400	408	12V DC	248,500	HP3035G	47"x31"x41"	445
1065SSE CAL†	1.110-089.0	3.5	3000	Vanguard 400	408	12V DC	309,900	HS3540G.3	47"x31"x45"	510
1075SSE†	1.110-012.0	4.0	3500	Honda GX390	389	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075SSE CAL†	1.110-080.0	4.0	3500	Vanguard 400	408	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075BE Compact†	1.110-088.0	4.0	3500	Vanguard 400	408	12V DC	309,900	HM4035	47"x31"x45"	520
1075BE Compact†	1.110-099.0	4.0	3500	Honda GX390	389	12V DC	309,900	HM4035	47"x31"x45"	520

*Battery not required † 12V battery required, but not supplied E = Electric-start engine B= Belt

**NEW BELT
DRIVE MODELS
1075BE -
COMPACT!**

HOTSY.COM

NOTHING CLEANS LIKE A HOTSY!

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2024 Kärcher North America
P/N HOT_GasEngineRollCage Effective 01/24

Distributed by: